

**RECEIVED
CENTRAL FAX CENTER****DEC 08 2004****Customer No.: 31561
Application No.: 10/605,080
Docket No.: 11221-US-PA****In The Claims:**

Claim 1. (Original) A two phase internal voltage generator, comprising
a first phase internal voltage generator for providing a first internal voltage source
upon receiving an external voltage source; and
a second phase internal voltage generator for providing a second internal voltage source,
the second phase internal voltage generator consumes relatively lower power than the first
phase internal voltage generator;
wherein as the second internal voltage source that is provided by the second phase
internal voltage generator is steadied, the first internal voltage source that is supplied by
the first phase internal voltage generator is cut off thereby.

Claim 2. (Original) The two phase internal voltage generator as recited in claim 1,
the second internal voltage generator comprises:
a voltage pump generator, for pumping up voltage of the external voltage source for
providing a pumped voltage according to a first control signal;
an input gate voltage generator, coupling to the voltage pump generator, for stepping-
down and regulating the pumped voltage to an input gate voltage; and
a power output circuit, coupling to the input gate voltage generator, for steadily
providing the second internal voltage source according to the input gate voltage.

BEST AVAILABLE COPY

Customer No.: 31561
Application No.: 10/605,080
Docket No.: 11221-US-PA

Claim 3. (Original) The two phase internal voltage generator as recited in claim 2, the first phase internal voltage generator cuts off the first internal voltage source supplied by the first phase internal voltage generator according to a third control signal.

Claim 4. (Cancelled)

Claim 5. (Original) The two phase internal voltage generator as recited in claim 2, the power output circuit comprising a power transistor, wherein the gate terminal of the power output circuit couples to the input gate voltage, a first source/drain terminal power output circuit couples to the external voltage source, and a second source/drain terminal power output circuit outputs the second internal voltage source.

Claim 6. (Original) The two phase internal voltage generator as recited in claim 5, wherein the power transistor is an NMOS power transistor.

Claim 7. (Original) The two phase internal voltage generator as recited in claim 1, wherein the first phase internal generator comprises:

a comparator, for comparing a reference voltage and a feedback voltage, outputting a control voltage;

a power transistor, wherein the gate terminal of the power transistor couples to the control voltage, the first source/drain terminal of the power transistor couples to the external voltage source, and the second source/drain terminal of the power transistor couples to the first internal voltage source;

Customer No.: 31561
Application No.: 10/605,080
Docket No.: 11221-US-PA

a first resistor, having a first terminal and a second terminal, wherein the first terminal couples to the second source/drain terminal of the power transistor; and

a second resistor, having a first terminal and a second terminal, wherein the first terminal couples to the second terminal of the first resistor so as to provide the feedback voltage, and the second terminal is grounded.

Claim 8. (Currently Amended) A two phase internal voltage generating method, being applied to an integrated circuit having a first phase internal voltage generator and a second phase internal voltage generator wherein the second phase internal voltage generator consumes relatively lower power than the first phase internal voltage generator, the steps of the two phase internal voltage generating method successively comprise:

a first internal voltage source being promptly provided by the first phase internal voltage generator upon receiving an external voltage source;

an input gate voltage obtaining from stepping-down and regulating a pumped voltage that is obtained from pumping the external voltage source generated by the second internal voltage generator, and a second internal voltage source being provided according to the input gate voltage; and

the first internal voltage source, supplied by the first phase internal voltage generator, being cut off when the second internal voltage source is steadied

Claim 9. (Original) The two phase internal voltage generating method as recited in claim 8, wherein the second phase internal voltage generator comprises:

Customer No.: 31561
Application No.: 10/605,080
Docket No.: 11221-US-PA

a voltage pump generator, for providing the pumped voltage that is pumped up from voltage of the external voltage source according to the first control signal;

an input gate voltage generator, coupling to the voltage pump generator, for stepping down and regulating the pumped voltage to the input gate voltage according to a second control signal; and

a power output circuitry, coupling to the input gate voltage generator, for steadily providing the second internal voltage source according to the input gate voltage.

Claim 10. (Original) The two phase internal voltage generating method as recited in claim 9, wherein the first phase internal voltage generator cuts off the first internal voltage source supplied by the first phase internal voltage generator according to a third control signal.

Claim 11. (Currently Amended) ~~The~~ A two phase internal voltage generating method ~~as recited in claim 10, being applied to an integrated circuit having a first phase internal voltage generator and a second phase internal voltage generator wherein the second phase internal voltage generator consumes relatively lower power than the first phase internal voltage generator, the steps of the two phase internal voltage generating method successively comprise:~~

a first internal voltage source being promptly provided by the first phase internal voltage generator upon receiving an external voltage source;

Customer No.: 31561
Application No.: 10/605,080
Docket No.: 11221-US-PA

an input gate voltage obtaining from stepping-down and regulating a pumped voltage that is obtained from pumping the external voltage source generated by the second internal voltage generator, and a second internal voltage source being provided according to the input gate voltage; and

the first internal voltage source, supplied by the first phase internal voltage generator, being cut off,

wherein the second phase internal voltage generator comprises:

a voltage pump generator, for providing the pumped voltage that is pumped up from voltage of the external voltage source according to the first control signal;

an input gate voltage generator, coupling to the voltage pump generator, for stepping down and regulating the pumped voltage to the input gate voltage according to a second control signal; and

a power output circuitry, coupling to the input gate voltage generator, for steadily providing the second internal voltage source according to the input gate voltage,

wherein the first phase internal voltage generator cuts off the first internal voltage source supplied by the first phase internal voltage generator according to a third control signal,

wherein the steps successively comprise:

the first internal voltage source being promptly provided by the first phase internal voltage generating method upon receiving the external voltage source;

Customer No.: 31561
Application No.: 10/605,080
Docket No.: 11221-US-PA

the first control signal being actuated, so as to activate the voltage pump generator to provide the pumped voltage;

the second control signal being actuated, so as to activate the input gate voltage generator to output the input gate voltage as well as to activate the power output circuitry to steadily provide the second internal voltage source; and

the third control signal being actuated, so that the first internal voltage source supplied by the first phase internal voltage generator is cut off.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.